



PRODUCT SPECIFICATIONS

DX12™

DX12 is a medium weight, general-purpose blended poly/cotton canvas which is especially suitable for a wide range of applications. These include: swags, marquee and tepee roofs and walls, temporary shelters, under tarpaulins, box-trailer covers and heavy-duty campervan roofs and walls. DX12 is also perfect for annexe roofs in semi-permanent situations, as well as high quality family marquee roofs and walls.



WEIGHT:	Loomstate: 410g/sq.m (12.1 oz) +/- 30gsm Dynaproofed: 505g/sq.m (14.9 oz) +/- 30gsm
WIDTH:	Loomstae: 210cm Dynaproofed: 204cm
CONSTRUCTION:	Woven 52/48 Poly/Cotton Plain Weave 22.8 ends per cm. 15 picks per cm. Yarn Count 2/12 ECC x 2/12 ECC
Maximum Shrinkage	2.5% in Warp
Tear Resistance: (AS 2001.2.10)	WARP - 116N WEFT - 68N
Breaking Force (AS 2001.2.3)	WARP - 2195N WEFT - 1523N
Hydrostatic Head: (AS 2001.2.17)	800mm min
Cone Test: (AS 2001.2.18)	Pass
Stock Colours:	Antelope, Beige, Black, Blue, Green, Brunswick Green, Dark Green, Grey, Khaki, Lt. Grey, Lt. Sand, Maroon, Navy, Olive, Olive F/R and Aus Cam D.P.
Flammability:	Olive F/R tested to AS1530 Part 3 Results available on request